

		SDR 33			SDR 26			SDR 21		
Rigidez del anillo		SN 2			SN 4			SN 8		
Diam. Nominal	Diam. Nominal	Diám. Int. mm	Esp. mm	Peso Kg/m	Diám. Int. mm	Esp. mm	Peso Kg/m	Diám. Int. mm	Esp. mm	Peso Kg/m
Ø mm	Nominal	MIN	MIN	MAX	MIN	MIN	MAX	MIN	MIN	MAX
110	4"	-	-	-	100.2	4.20	1.550	97.8	5.30	1.908
125	5"	-	-	-	114.0	4.80	1.979	111.2	6.00	2.454
160	6"	148.80	4.90	5.80	145.8	6.20	3.268	142.6	7.70	3.963
200	8"	185.80	6.20	7.35	182.6	7.70	5.009	178.4	9.60	6.150
250	10"	232.60	7.70	9.00	228.4	9.60	7.776	223.4	11.90	9.477
315	12"	293.2	9.70	9.977	287.8	12.10	12.34	281.4	15.00	15.08
355	14"	330.6	10.90	12.59	324.6	13.60	15.54	315.6	16.90	19.88
400	16"	372.4	12.30	16.04	365.8	15.30	19.70	355.6	19.10	25.24
450	18"	419.2	13.80	20.14	410.0	17.20	25.88	400.4	21.50	31.74
500	20"	465.8	15.30	24.85	455.6	19.10	31.92	445.2	23.90	38.97
630	24"	585.0	19.30	41.13	574.0	24.10	50.73	560.6	30.00	62.18

↘ Fotos referenciales para esta norma.

